THE DP-7000 HIGH RES PRE-PROOF PRINTER

→ TECHNICAL FEATURES

Oki, Network Solutions for a Global Society

OKI

DP-7000 Technical Features

The DP-7000 prints high quality A3+ proofs on final Press Media, not only with the standard CMYK process colours, but with Silver, Gold, White, Varnish, Red, Green and Blue spot colours too.

Designed for use by professional graphic designers and print houses, the DP-7000 offers print quality comparable to an offset press with very accurate colour reproduction at 160 lpi and 2400 dpi. Quick, easy and economical to use it is perfect for creating design concepts at your desktop.

Macintosh Postscript level 3 driver software included.

PRINTING METHOD	Serial thermal transfer
PRINTER HEAD	240 dots Micro Deposit On Silicon (DOS) Head
PRINTING SPEED **A3 image**	Equivalent to 235 cps 7mins 30secs: 600 dpi standard CMYK colour 16mins 30secs: 2400 dpi VPhoto printing CMYK colour
POSTSCRIPT DRIVER	Macintosh Adobe PS level 3 SoftRIP driver included SCSI: Mac OS 8.1 or later (OSX not supported) USB: Mac OS 8.5 or later (OSX not supported) 64 MB free RAM required, 90 Mhz 601 Power PC min Supports printing across a network via a host ICC compatible
RESOLUTION	Prints A3+ colour images at: 2400 x 2400 dpi (VPhoto printing) equivalent 1200 x 600 dpi Mono, 600 x 600 dpi standard
MEDIA	Press Paper-Matt, Press Paper-Art, VPhoto Film, Transparency Film, Transfer Film, Card
INK CASSETTE HOLDERS	Up to 9 at a time
INK CASSETTE	Instantaneously dry, pigment-based inks (waterproof and anti-UV) Cassettes are bar-coded to ensure ease of use
Process	Cyan, Magenta, Yellow, Black
Metallic (opaque)	Gold, Silver, Magenta, Cyan
Lustre Foil	Gold, Silver
Spot Colour	Opaque White, Red, Green, Blue, Black, Finish II
PAPER CAPACITY	100 sheets (Plain Paper), 30 sheets (Press Paper), 30 sheets (High Grade Paper), 1 sheet (VPhoto Film)
PRINTABLE AREA	322.4mm x 654mm maximum
PAPER FEED METHOD	Friction Feed
PAPER SIZE	98mm x 98mm to 330.2mm x 681mm, cut sheet
PAPER THICKNESS	0.07mm to 0.23mm (A4), 0.07mm to 0.1mm (A3)
DIMENSIONS	568mm x 270mm x 202mm (W x D x H)
WEIGHT	9.5 kg
POWER SUPPLY	AC 100V-240V 50Hz/60Hz
INTERFACES	USB SCSI adapter supplied as standard
NOISE	51dBA or less
ENERGY EFFICIENCY	This product meets the Energy Star guidelines for energy efficiency
SAFETY AND ELECTROMAGNETIC COMPATIBILITY	This product complies with the requirements of the Council Directives 89/336/EEC and 73/23/EEC amended by 93/68/EEC on the approximation of the laws of the member states relating to electromagnetic compatibility and low voltage
OPERATING ENVIRONMENT	
Temperature	5-35 degrees Centigrade
Humidity	30-70%

European Head Office
Oki Europe Limited
Central House
Balfour Road
Hounslow
Middlesex
TW3 1HY
United Kingdom

Telephone +44 (0)20 8219 2190
Facsimile +44 (0)20 8219 2199
www.okieurope.com

OKI

Specifications subject to change without notice. All trademarks acknowledged